



28160050 FULL COMPACT

masking waterborne paint for interiors



A masking waterborne paint for interiors. Its high opacity and masking power make it the ideal choice for cover imperfections of walls, also on broad surfaces. Thanks to its rapid drying time, it can be applied in any season of the year and the paint job can be completed within a short time. FULL COMPACT is formulated with a low VOC content for ecological reasons, to respect the environment.



Date of revision	09/11/2021
Composition	Single-component, physically drying matt vinyl paint in aqueous dispersion for the finishing coat. Classification as per UNI 8681: B4.C.0.A.2.HA
Main properties	<ul style="list-style-type: none"> dries rapidly conceals imperfections high opacity excellent breathability
Applications	In building works as a breathable waterborne paint for interiors, features high breathability. The product is specially formulated for professional use.
Colour	Bianco Base.

Technical specifications (data measured at 20°C, with 65% R.H.)	Reference	UoM	Value
Specific weight (pycnometer)	C022	kg/l	1.650 ± 0.050
pH	C030		8.7 ± 0.3
Brookfield viscosity @ 200 rpm	C054	cP	8000 ± 500

Method of use	
. Surface and application conditions	Ambient temperature min +5°C / max +35°C R.H. < 80%. Surface temperature min +5°C / max +35°C R.H. < 10%.
. Application method	Brush, roller, airless.
. Thinner	Water.
. Dilution	Roller 20–25%, brush 20–40%, airless 25–40%.
. Mixing	Mix the product with care, adding water gradually until you reach the correct viscosity.
. Theoretical coverage	12–14 m ² /l per coat, depending on the absorbency of the support.

Rival is a trademark of
Colorificio Sammarinese S.p.A.
Via del Camerario 7
47891 Falciano, San Marino
T +378 (0549) 905 515
F +378 (0549) 908 453
colorificio@colsam.com
colsam.com

C.o.e. SM00026
Fully paid-up share capital € 3,000,000.00
Legal title
no. 26 dated 20 May 1944



Application cycle

On new or painted load-bearing supports:

make sure that the support has been seasoned for at least 30 days, is perfectly cohesive and is totally free of dust or dirt. Then apply one coat of Fissa e Colora appropriately diluted.

On old and/or sandy supports:

treat the support with Fissacril Forte suitably diluted.

On supports painted with non-load-bearing and flaking finishes:

remove any unstable parts by means of a power wash or stripping, then leave the surface to dry and strengthen the plaster with Rivalfix ready-for-use.

On supports attacked by algae and moulds:

refurbish the wall using TITANSAN and leave it to take effect for 24/36 hours. Admix FULL COMPACT with the AM100 additive.

On plasterboard or walls with gypsum-based fillings:

apply Fissacril Forte suitably diluted.

Notes

Any hardened drops can be easily removed with Diluente Nitro 92100012 thinner.

Storage

Do not allow to freeze; store between +5°C and +20°C. Once opened, the undiluted product can be kept for 3 months in the closed container stored in the dark.

Warnings

Wash brushes and tools immediately after use; do not dump the wash water on the ground or into groundwater.

Keep out of reach of children.

For further information, consult the safety data sheet.

VOC Classification - Directive 2004/42/EC - Italian Legislative Decree no. 161/2006

A/A -, maximum 30 g/l (2010).

Maximum VOC content of FULL COMPACT ready for use: 30 g/l.

Specification items

Apply 2 coats of FULL COMPACT masking waterborne paint for interiors in the colour desired by the work supervisor, after suitably preparing the surfaces to be treated. Includes materials and application, excludes skimming and/or scaffolding.

This information is the result of our practical experience but is purely indicative. For more detailed information, please contact our technical support service. This sheet cancels and substitutes any previous editions.
